

EXEAT · COMMERCIAL

LIO 280 Pro

Up to 30 kg per batch · 11 stainless-steel trays · 3.9 m² shelf area. European-built, CE-certified professional freeze dryer. LIO 280 L hardware plus advanced process control — repeatable, higher-throughput, sensitive-product ready. Oil-sealed pump standard; oil-free scroll option.



BATCH CAPACITY

30 kg

AVG. ENERGY USE

3.59 kWh / h

SHELF AREA

3.9 m²

APPLICATIONS

Freeze-Drying for Fruits & Vegetables

Freeze-Drying for Nutraceuticals & Supplements

Freeze-Drying for Confectionery

Freeze-Drying for Ready Meals & Snacks

CE marked

Built in EU

Why choose the LIO 280 Pro

- ✓ **For established production lines** — largest of the LIO range, for producers running regular commercial batches.
- ✓ **Up to 30 kg fresh load** — 11 trays, 3.9 m² shelf area.
- ✓ **Top-configured, ready to run** — the Pro build with the deep-vacuum pump option, for users who want the full-performance setup out of the box.
- ✓ **Repeatable results** — controlled shelf temperature and deep vacuum for consistent structure, colour and rehydration. CE-certified, AISI 304 stainless, 12-month warranty.

CAPACITY & OUTPUT

Batch capacity (fresh load)	30 kg
Ice condenser capacity	48 kg
Total shelf area	3.9 m²
Number of shelves / trays	11
Shelf spacing	37 mm
Tray size	39 × 91 cm

PROCESS & CYCLE

Shelf temperature range	-35 to +60 °C (recipe)
Min. condenser temperature	-43 °C
Defrosting	Automatic / fast defrost (Pro)
Defrost time	1 h

VACUUM & REFRIGERATION

Vacuum pump	Oil-sealed (oil-free scroll option)
Refrigeration	Air-cooled
Refrigerant	R290 (natural refrigerant, GWP 3)

CONTROL & MONITORING

Control system	PLC touchscreen + Pro: pressure control · pressure-building control · fast defrost · automatic drain control
Menu language	English
Data logging & recipes	USB CSV export + recipes
Remote monitoring	No

BUILD

Chamber / shelf material	AISI 304 stainless steel
--------------------------	---------------------------------

POWER & FOOTPRINT

Power supply	400 V / 3~ / 50 Hz
Connected load	4.24 kW
Energy consumption (avg)	3.59 kWh/h
External dimensions (W×D×H)	850 × 1050 × 1275 mm
Net weight	340 kg

WARRANTY & SERVICE

Warranty	12 months
----------	------------------

Recommended accessories

AMARU Mineral oil for vacuum pump 10 L	Fits: All
--	-----------

AMARU Mineral oil for vacuum pump 20 L	Fits: All
--	-----------

AMARU Viktor – Ozone decontaminator	
-------------------------------------	--

Leosmak High-Performance Vacuum Pump Oil	Fits: All Leosmak
--	-------------------

Moisture analyzer AXIS ATS60	Fits: All
------------------------------	-----------

More accessories are available in our online store — follow the QR code.



+34 614 332 324

team@freeze-drying.tech

freeze-drying.tech

Scan for live specifications, current pricing and to request a quotation.